

EXPERIMENTAL INVESTIGATION OF THE NONLINEAR
CHARACTERISTICS OF WHISTLER WAVES*

W. E. Amatucci¹, D. D. Blackwell², D. N. Walker¹
, G. Ganguli¹, G. Gatling²

¹Plasma Physics Division, Naval Research Laboratory, Wash-
ington, DC 20375

²SFA, Inc., Largo, MD 20774

Abstract Submission Form

2004 National Radio Science
Meeting

Abstract: amatucci22602

Date Received: September 23, 2004

Many interesting in situ and laboratory observations of whistler wave propagation and stimulated emissions have been made over the past few decades. In the space environment, observations of artificially stimulated emissions from the magnetosphere triggered by whistler modes launched from VLF transmitters have been reported by *Stiles and Helliwell* [1975]. The emission radiation is assumed to come from the temporary phase bunching of particles by the constant frequency triggering signal. In the laboratory, *Stenzel* [1975] reported on the self-ducting of large-amplitude whistler waves. Those experiments showed that with increasing driving amplitude, the radiation pattern from a small dipole antenna becomes increasingly narrow, and ultimately forms a duct with diameter of the order of the parallel wavelength within which the waves propagate virtually undamped.

Observations such as these have prompted an NRL Space Physics Simulation Chamber investigation of nonlinear whistler wave dynamics in a simulated radiation belt environment. The ultimate goals are to understand and quantify ducting, self-focusing, and amplification of whistler waves, to investigate nonlinear whistler-plasma interactions, and to study the secondary emission of whistler waves. In the initial experiments, transmitting and receiving magnetic loop antennas and crossed electric field dipole receiving antennas have been fabricated and tested. Electromagnetic modes launched in the Space Chamber plasma have been identified as whistler waves due to the correspondence of the wave properties with theoretical predictions. Preliminary investigations into the nonlinear properties of whistler have provided indication of whistler wave ducting.

Space Chamber experiments are also underway to characterize the radiation resistance of different whistler wave antenna geometries, beginning with an investigation of the radiation characteristics of a spherical capacitive probe. Initial results from these experiments confirm the accuracy and performance of the plasma diagnostics by identification of the electron plasma frequency. Simplified plasma models are used to help guide the experimental effort.

*Work supported by the Office of Naval Research and DARPA.

Stiles, G. S. and R. A. Helliwell, *J. Geophys. Res.*, **80**, 608 (1975).
Stenzel, R.L., *Phys. Rev. Lett.*, **35**, 574 (1975).

1. (a) Bill Amatucci
Plasma Physics Division
Code 6755
Naval Research Laboratory
Washington, DC
20375 USA
amatucci@ccf.nrl.navy.mil
- (b) 202-404-1022
- (c) 202-767-3553
2. H - Waves in Plasma
3. (a) Radiation Belt
4. C - Contributed Paper,
Program chair: Greg Ginat
5. No special instructions