

Thermo Scientific Model 42i-Y NO_y Analyzer



Key Features

- Ethernet connectivity for efficient remote access
- Enhanced user interface with one button programming and large display screen
- Flash memory for increased data storage and user downloadable software
- Enhanced electronics design optimizes product commonality
- Improved layout for easier accessibility to components

The Thermo Scientific Model 42i-Y NO_y Analyzer utilizes chemiluminescence technology to measure the amount of nitrogen oxides in the air from sub-ppb levels up to 1000 ppb.

The Model 42i-Y analyzer is a single chamber, single photomultiplier tube design that measures NO_y which includes most oxides of nitrogen with the exception of NH₃ and N₂O.

Dual range and auto range are standard features in this instrument. Because the instrument is operated continuously in the NO_y mode, the response time is less than 10 seconds.

Temperature and pressure correction are standard features. User settable alarm levels for concentration and for a wide variety of internal diagnostics are available from an easy to follow menu structure.

This state-of-the-art gas analyzer offers features such as an ethernet port as well as flash memory for increased data storage and field upgradability.

Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

You can easily program short-cut keys allowing you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display measurement information and status, while viewing menu and operational screens.

Product Specifications

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

Thermo Scientific Model 42i-Y NO_y Analyzer

Preset Ranges	0-5, 10, 20, 50, 100, 200ppb and 0-10, 20, 50, 100, 200 and 500, 1,000 and 2,000 µg/m ³ to 0-10, 20, 50, 100, 200 µg/m ³
Zero Noise	< 25 ppt RMS (120 second averaging time)
Lower Detectable Limit	< 50 ppt (120 second averaging time)
Zero Drift (24 hour)	Negligible
Span Drift (24 hour)	+/- 1% full scale
Response Time	60 sec (10 second averaging time)
Linearity	+/- 1% full scale
Sample Flow Rate	1 LPM
Operational Temperature	59° to 95° F (15° to 35° C) Performance or 32° to 113° F (0° to 45° C) Operating
Power Requirements	100 VAC, 115 VAC, 220-240 VAC +/-10% @ 300W
Size and Weight	16.75"(W) x 8.62"(H) x 23"(D), 55 lbs. / 425 mm (W) x 219 mm (H) x 584 mm (D), 25 kg
Outputs	Selectable Voltage, RS232/RS485, TCP/IP, 10 Status Relays, and Power Fail Indication (standard). 0-20 or 4-20 mA Isolated Current Output (optional)
Inputs	16 Digital Inputs (standard), 8 0-10vdc Analog Inputs (optional)

Ordering Information

Model 42i-Y NO_y Analyzer

Choose from the following configurations/options to customize your own Model 42i-Y

1. Voltage options:

A = 115 VAC 60 Hz
B = 220/240 VAC 50Hz
C = 220 VAC 60 Hz
D = 115 VAC 50 Hz
J = 100 VAC 50/60 Hz

2. Internal zero / span:

N = No zero / span assembly (standard)
Z = Internal zero span assembly

3. Converter options:

M = Molybdenum (standard)

4. Sample handling:

S = Standard plumbing (standard)

5. Ozone handling:

D = Drierite scrubber (standard)
P = Permeation dryer

6. Optional I/O:

A = None (standard)
C = I/O expansion board
(4-20mA outputs - 6 channels, 0-10v inputs - 8 channels)

7. Mounting Hardware:

A = Bench mounting (standard)
B = Ears & handles, EIA
C = Ears & handles, Retrofit

Other options:

- ◆ Teflon particulate filter
- ◆ Ozone particulate filter
- ◆ Rack mounts
- ◆ Rear extender

Your Order Code: 42i-Y-_____

Lit_42iYAQL_10/10

© 2010 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries.

This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

Air Quality Instruments

27 Forge Parkway
Franklin, MA 02038 USA

(866) 282-0430
(508) 520-0430
(508) 520-1460 fax

www.thermoscientific.com/AQI

Thermo
SCIENTIFIC